

B.

Clout

You've got Clout, so stand strong and make a difference. This homogenous vinyl composite quartz tile offers strength and endurance, which are essential in commercial, educational, housing, and retail floors. Designers can create a great look with a white marbling effect in 7 modern colours, of which 4 are available in 2 thicknesses. Clout is proudly made in Africa to ISO and SANS standards and is 100% recyclable, which makes it an even more powerful choice.

Extended Specifications


Use Classification:	Heavy Commercial
Total Mass:	±3.8 (kg/m ²) ±4.75 (kg/m ²)
Total Thickness:	2.0 (mm) 2.5 (mm)
Tile Size (l x w):	300mm x 300mm
Quantity Per Box:	50 tiles per box (4.5m ²) 40 tiles per box (3.6m ²)
Chemical Resistance:	Good resistance to everyday substances. Advice is available on resistance to specific chemicals and dilution.
Fire Index:	1 (SANS 10177-4)
Indentation:	Pass (suitable for intensive use - SANS 581)
Residual Indentation:	Pass (excellent recovery from indentation- SANS 581)
Static Electrical Charge:	Classified as electrically insulating. Not conductive or anti-static in nature.
Underfloor Heating:	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
VOC Emissions - Green Building Specifications):	0.01µg/m ² /hour



B.




Biltong |
2 & 2.5mm




Boulders |
2 & 2.5mm



Gansbaai | 2mm



Mining | 2mm



Rooibos |
2 & 2.5mm



Safari | 2mm



Table Mountain |
2 & 2.5mm

Clout



Medium/General
Commercial



Heavy
Commercial



From Local &
Imported Goods



Institution



Underfloor
Heating



Suitable for
Staircases



Hospitality



Modular



LIMITED WEAR WARRANTY
15
YEAR



bsi
ISO 9001
Quality
Management
Systems
CERTIFIED

Bill of Quantities

- Belgotex CLOUT 30x30cm Heavy Commercial flexible vinyl composite quartz tiles are available in 2mm and 2.5mm total thickness.
- 15 year limited wear warranty.
- Manufactured in accordance with SANS 581 on a prepared Class 1 sub floor in accordance with SANS 10070.
- The newly laid floor must, after 72 hours, be stripped and sealed.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.