

B.

Centra 70

Unyielding Resilience

Centra 70 offers an affordable, high-performance flooring solution with its durable multi-layer construction and a 0.70 mm wear layer, ideal for projects where performance is key. The Hyperguard+ finish provides low maintenance and scratch resistance, ensuring a resilient, easy-to-maintain surface that can withstand heavy use wherever needed.

Extended Specifications

Type of Installation:	Multi Layered vinyl flooring with compact backing – Fully Glued
Use Classification: (EN 1307)	Heavy Commercial
Total Weight: (ISO 23997)	2543 (g/m ²) 75.00 (oz/yd ²)
Wear Layer Thickness: (ISO 24340)	0.70 (mm) 0.027 (in)
Total Thickness: (ISO 24346)	2.0 (mm) 0.078 (in)
Product Width:	2 (m) 78.74 (in)
Pattern repeat:	(Refer to details in table below)
Roll Size:(l x w)	25 x 2 (m) 984.25 x 78.74 (in)
Backing Type:	Compact Backing



B.

Extended Specifications

PUR Treatment:	Hyperguard +
Abrasion group:	Group T
Chemical Resistance: (EN ISO 26987)	Good
Fire Classification: (EN 13501-1)	Bff-s1
Slip Resistance: (DIN 51130)	R10
Residual Indentation: (EN ISO 24343-1)	0.05mm
Thermal Conductivity: (EN 12667)	0.190W/m.K
Electrostatic Behaviour: (Body Voltage Test) (EN 1815 Method A)	≤ 2kV
Dimensional Stability: (EN ISO 23999)	≤0.05%
Colour Fastness: (ISO 105-B02)	>6
Sound Absorption: (EN ISO 717/2)	Δ Lw 7 dB
Heating Insulation: (EN 12664)	0.0080m ² k/W
Castor Chair: (EN ISO 4918)	Type W
Underfloor Heating: (EN 12524)	Suitable
Total VOC Emissions:	Low concentration of VOC
Warranty:	7 years



B.

Centra 70

Unyielding Resilience



Allure T43

Pattern repeat:
99.5cm x 120cm



Allure T45

Pattern repeat:
99.5cm x 120cm




Calais T34

Pattern repeat:
100cm x 120cm



Camargue T51

Pattern repeat:
100cm x 120cm



London Stone T93

Pattern repeat:
200cm x 100cm



London Stone T94

Pattern repeat:
200cm x 150cm




Sedna T32

Pattern repeat:
100cm x 100cm



Sedna T94

Pattern repeat:
100cm x 100cm



Bill of Quantities

- Belgotex CENTRA 70 2.0mm Heavy Commercial Use Multi Layered vinyl flooring with compact backing – Fully Glued
- 25 x 2m with 0.70mm wear layer.
- 7 year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- Green tag level A Gold rated certification

Note: Belgotex offers customization of this product in colour. Please contact a Belgotex representative for more information.

Product characteristics may vary due to the nature of manufacturing. To combat colour variance do not install more than one dye lot in a single installation. Sample swatches have been cut from an overall design; therefore, the decoration and shades may vary. A difference in appearance from the pattern is likely, as the product is not intended to have a uniform appearance.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.