

# B.

## Oak Trifecta Medium

### The Oak Advantage

Get three times more with Trifecta: an ultra-realistic oak wood look, durability, and 3 plank sizes! Optimise the ideal size to enhance your design. Trifecta Medium is available in a plank size of 1219.2mm x 177.8mm (l x w), ideal for smaller spaces. A home win choice.

### Extended Specifications

Type of Installation:	Dry Back (Stick Down)
Use Classification: (EN1307)	Heavy Residential
Wear Layer Thickness:	0.30 mm   0.011 in
Total Thickness: (ISO 8543)	2.0 mm   0.078 in
Tile Size (l x w):	1219.2 x 177.8 mm   48 x 7 in
Quantity Per Box:	4.34m <sup>2</sup>
Chemical Resistance: (EN ISO 26987)	Yes
Fire Classification: (EN 13501-1)	Bfl-s1
Slip Resistance: (DIN 51130)	R10



# B.

## Oak Trifecta Medium

The Oak Advantage

### Extended Specifications

Residual Indentation: (EN ISO 24343-1)	<0.1mm
Thermal Resistance: (EN 12664)	0.028(mK)/W
Electrostatic Propensity: (Body Voltage Test) (EN 1815 Method A)	0.1kV
Dimensional Stability: (EN ISO 23999)	≤0.25%
Colour Fastness: (ISO 105-B02)	>6 Grade
Sound Absorption: (EN ISO 10140-3)	Approx. 3 dB
Castor Chair Suitability: (EN ISO 4918)	Yes, Type W
Floor Heating System:	Yes, max 27°C
VOC Emissions:	Floorscore SCS-FS-03336
Warranty:	20 years
Sustainability:	Floorscore



# B.

## Oak Trifecta Large

### The Oak Advantage

Get three times more with Trifecta: an ultra-realistic oak wood look, durability, and 3 plank sizes! Optimise the ideal size to enhance your design with the added functionality of mixing and matching. Trifecta Large offers a plank format that is a great solution for the average room size at 1219.2mm x 228.6mm (l x w). A home win choice.

### Extended Specifications

Type of Installation:	Dry Back (Stick Down)
Use Classification: (EN1307)	Heavy Residential
Wear Layer Thickness:	0.30 mm   0.011 in
Total Thickness: (ISO 8543)	2.0 mm   0.078 in
Tile Size (l x w):	1219.2 x 228.6 mm   48 x 9 in
Quantity Per Box:	4.18m <sup>2</sup>
Chemical Resistance: (EN ISO 26987)	Yes
Fire Classification: (EN 13501-1)	Bfl-s1
Slip Resistance: (DIN 51130)	R10



# B.

## Oak Trifecta Large

The Oak Advantage

### Extended Specifications

Residual Indentation: (EN ISO 24343-1)	<0.1mm
Thermal Resistance: (EN 12664)	0.028(mK)/W
Electrostatic Propensity: (Body Voltage Test) (EN 1815 Method A)	0.1kV
Dimensional Stability: (EN ISO 23999)	≤0.25%
Colour Fastness: (ISO 105-B02)	>6 Grade
Sound Absorption: (EN ISO 10140-3)	Approx. 3 dB
Castor Chair Suitability: (EN ISO 4918)	Yes, Type W
Floor Heating System:	Yes, max 27°C
VOC Emissions:	Floorscore SCS-FS-03336
Warranty:	20 years
Sustainability:	Floorscore



# B.

## Oak Trifecta XL

### The Oak Advantage

Get three times more with Trifecta: an ultra-realistic oak wood look, durability, and 3 plank sizes! Optimise the ideal size to enhance your design with the added functionality of mixing and matching. Trifecta XL offers a luxurious-looking solution for large spaces with planks sized at 1516.8 x 241.3 mm (l x w). A home win choice.

### Extended Specifications

Type of Installation:	Dry Back (Stick Down)
Use Classification: (EN1307)	Heavy Residential
Wear Layer Thickness:	0.30 mm   0.011 in
Total Thickness: (ISO 8543)	2.0 mm   0.078 in
Tile Size (l x w):	1516.8 x 241.3 mm   59.72 x 9.5 in
Quantity Per Box:	4.34m <sup>2</sup>
Chemical Resistance: (EN ISO 26987)	Yes
Fire Classification: (EN 13501-1)	Bfl-s1
Slip Resistance: (DIN 51130)	R10



# B.

## Oak Trifecta XL

The Oak Advantage

### Extended Specifications

Residual Indentation: (EN ISO 24343-1)	<0.1mm
Thermal Resistance: (EN 12664)	0.028(mK)/W
Electrostatic Propensity: (Body Voltage Test) (EN 1815 Method A)	0.1kV
Dimensional Stability: (EN ISO 23999)	≤0.25%
Colour Fastness: (ISO 105-B02)	>6 Grade
Sound Absorption: (EN ISO 10140-3)	Approx. 3 dB
Castor Chair Suitability: (EN ISO 4918)	Yes, Type W
Floor Heating System:	Yes, max 27°C
VOC Emissions:	Floorscore SCS-FS-03336
Warranty:	20 years
Sustainability:	Floorscore



# B.



Bur Oak - XL



Cork Oak - XL



Pin Oak - XL



Shumard Oak - XL

# Oak Trifecta XL

## The Oak Advantage



### Bill of Quantities

- Belgotex OAK TRIFECTA - XL 2.0m Heavy Residential Dry Back Stick Down LVT vinyl.
- Available in 1516.8 × 241.3mm with 0.3mm wear layer.
- 20-year residential warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- Green tag level A Gold rated certification.

\*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.